

Beta Swift

ADKINS

HEAT PRESS TECHNOLOGY



A. Adkins and Sons Limited
High Cross,
Lancaster Road,
Hinckley
Leicestershire
LE10 0AW
United Kingdom

Tel: + 44 (0) 1455 89 12 91

Fax: + 44 (0) 1455 63 35 03

Email: service@adkins.com

sales@adkins.com

Web: www.adkins.com

Beta Swift

The Beta Swift is a manually-operated table top transfer press, which is particularly suitable for laundry marking/fusing and label application, as well as general usage.

This fully portable machine can be used virtually anywhere, simply plug it in. It's unique state of the art advanced computerised controller accurately monitors both temperature and time, to make it a world leader.

Initially designed for use in the laundry industry, the Beta Swift has now been developed for more wide ranging use.

Featuring a strong, light, aluminium construction, the Swift is fitted with self-aligning spring mounted silicone pressure pad to ensure correct pressure and an audible buzzer on the timer mechanism. The simple, robust machine is powered by a microprocessor for control of both heat and dwell accuracy and ease of operation and requires minimal operating space.

Each Swift Press is produced in two versions, nominally 230-240 Volts AC for the European market and 120 Volts AC for the American market.

The models 135, 153 and 205 vary only in the size of their heat plates, pressure pad assemblies and their power ratings.

Specifications	European Machines		
	135	153	205
Power Consumption	500 Watts	1000 Watts	1100 Watts
Power Supply	230-240 Volts AC	230-240 Volts AC	230-240 Volts AC
Working temperature	70-235°C	70-235°C	70-235°C
Display Timer Range	0 - 9.59 mins	0 - 9.59 mins	0 - 9.59 mins
Machine height open	61 cms	61 cms	61 cms
Machine height closed	28 cms	28 cms	28 cms
Machine width	23 cms	23 cms	23 cms
Machine depth	47 cms	47 cms	47 cms
Work area required	22 x 61 x 43 cms		
Weight export packed	14 kg	15 kg	16 kg
Size export packed	55(L) x 29(W) x 33 cms(H)		
Net weight	10 kg	11 kg	12 kg
Press pad dimensions	13.5 x 9.5 cms	15.3 x 15.3 cms	20.5 x 20.5 cms
Fuses	3.15 A	6.3 A	6.3 A
A-weighted noise level	<70 dB(A)	<70 dB(A)	<70 dB(A)

Specifications	USA Machines		
	135	153	205
Power Consumption	500 Watts	1000 Watts	1100 Watts
Power Supply	120 Volts AC	120 Volts AC	120 Volts AC
Working temperature	160-455°F	160-455°F	160-455°F
Display Timer Range	0 - 9.59 mins	0 - 9.59 mins	0 - 9.59 mins
Machine height open	24 ins	24 ins	24 ins
Machine height closed	11 ins	11 ins	11 ins
Machine width	9 ins	9 ins	9 ins
Machine depth	18.5 ins	18.5 ins	18.5 ins
Work area required	8.6 x 24 x 17 ins		
Weight export packed	31 lbs	33 lbs	35 lbs
Size export packed	21.5(L) x 11.5(W) x 13 ins(H)		
Net weight	22 lbs	24 lbs	26 lbs
Press pad dimensions	5.25 x 3.75 ins	6 x 6 ins	8 x 8 ins
Fuses	6.3 A	12.5 A	12.5 A
A-weighted noise level	<70 dB(A)	<70 dB(A)	<70 dB(A)